

SUPER-FAST RECOVERY RECTIFIERS

REV:1.01

Features	Ultrafast 35 Nanosecond Recovery Time	Typical Reference Data VRRM= 200V IF(AV)= 8A VRRM= 400V IF(AV)= 8A VRRM= 600V IF(AV)=8A
	175° C Operating Junction Temperature	
	Popular TO-220AC Package	
	Epoxy Meets UL94 ,V0 @ 1/8"	
	High Temperature Glass Passivated Junction	
	Low Forward Voltage	
	Low Leakage Current	
Reverse Voltage to 600 Volts		
Pb-Free Packages are Available		

Mechanical Characteristics	Case: Epoxy, Molded
	Weight: 1.9 grams (approximately)
	Finish: All External Surfaces Corrosion Resistant and Terminal
	Leads are Readily Solderable
	Lead Temperature for Soldering Purposes: 260° C Max. for 10 Seconds
	Shipped 50 units per plastic tube

MAXIMUM RATINGS

Rating	Symbol	MUR820AC	MUR840AC	MUR860AC	Unit
Peak Repetitive Reverse Voltage	VRRM	200	400	600	V
Working Peak Reverse Voltage	VRRM				
DC Blocking Voltage	VR				
Average Rectified Forward Current Total Device, (Rated VR), TC = 150	IF(AV)	8			A
Peak Repetitive Forward Current (Rated VR, Square Wave, 20 kHz), TC = 150	IFM	16			A
Nonrepetitive Peak Surge Current (Surge applied at rated load conditions halfwave, single phase, 60	IFSM	100			A
Operating Junction Temperature and Storage Tempera	TJ, Tstg	- 40 to +175			

THERMAL CHARACTERISTICS(Per Diode Leg)

Maximum Thermal Resistance, Junction to Case	R _{JC}	3.0	2.0	MW
--	-----------------	-----	-----	----

ELECTRICAL CHARACTERISTICS(Per Diode Leg)

Maximum Instantaneous Forward Voltage (1) (IF = 8.0 Amps, TC = 25° C)	VF	1.05	1.35	1.5	V
Maximum Instantaneous Reverse Current (1) (Rated dc Voltage, TJ = 150° C)	IR	800	800	800	μ A
(Rated dc Voltage, TJ = 25° C)		10	10	10	
Maximum Reverse Recovery Time (IF = 0.5 A, IR = 1.0 A, IREC = 0.25 A)	Trr	35			ns

(1) Pulse Test: Pulse Width = 300μ s, Duty Cycle 2.0%.




Figure 1. Typical Forward Voltage




Figure 2. Typical Reverse Current




Figure 3 Current Derating, Case




Figure 4 Current Derating, Ambient




Figure 5 Power Dissipation




Figure 1. Typical Forward Voltage




Figure 2. Typical Reverse Current




Figure 3. Current Derating, Case




Figure 4. Current Derating, Ambient




Figure 5. Power Dissipation




Figure 1. Typical Forward Voltage




Figure 2. Typical Reverse Current




Figure 3. Current Derating, Case




Figure 4. Current Derating, Ambient





Figure 5. Power Dissipation

TO-220AC



注意事项:

- XXXX代表日期码，第一码表示公元年的最后一码，第二码表示生产时当月码 (A, B, C... 为一月，二月，三月...), 第三，四码表示大量生产时批次码。
例如: 2009年第一月生产的，D/C为9AXX。
- 包装及出货: ROHS, 30PCS/管, 0.6K/BOX, 1.8K(1.8K BOXEX)/CARTON, BOXEX及 CARTON。



MUR820AC



修订内容